

Limit thermostat, screwdriver adjustment and manual reset

CODE	ADJUSTMENT RANGE/ CALIBRATION	CONTACTS	BULB mm	BULB material	CAPILLARY mm	CAPILLARY material	PACK QTY
961-11228-00A *	90 ÷ 110 °C	ON/OFF	Ø 6.5 x 73	Cu	1000	Cu + PVC	50
961-11328-00A	90 ÷ 110 °C	ON/OFF + service	Ø 6.5 x 73	Cu	1000	Cu + PVC	50
961-11338-V0A	90 ÷ 110 °C	ON/OFF + service	Ø 6.5 x 73	Cu	1500	Cu + PVC	20
961-11338-00A	90 ÷ 110 °C	ON/OFF + service	Ø 6.5 x 73	Cu	1500	Cu + PVC	50
963-11328-V0A *	90 ÷ 110 °C	ON/OFF + service, gold plated	Ø 6.5 x 73	Cu	1000	Cu + PVC	20
963-11338-00A	90 ÷ 110 °C	ON/OFF + service, gold plated	Ø 6.5 x 73	Cu	1500	Cu + PVC	20
963-11338-03A	90 ÷ 110 °C	ON/OFF + service, gold plated	Ø 5 x 90	Cu	1500	Cu + PVC	20
961-90328-00A *	70 ÷ 90 °C	ON/OFF + service	Ø 6.5 x 73	Cu	1000	Cu + PVC	50
961-90338-00A *	70 ÷ 90 °C	ON/OFF + service	Ø 6.5 x 73	Cu	1500	Cu + PVC	50
963-90328-00A *	70 ÷ 90 °C	ON/OFF + service, gold plated	Ø 6.5 x 73	Cu	1000	Cu + PVC	50
963-90338-00A	70 ÷ 90 °C	ON/OFF + service, gold plated	Ø 6.5 x 73	Cu	1500	Cu + PVC	20
961-11338-20B * flue gas safety limiter version - with	70 ÷ 110 °C	ON/OFF + service	Ø 5 x 90	Cu	1500	Cu + PVC	50

washer and plate for bulb fixing							
963-11338-20B * flue gas safety limiter version - with washer and plate for bulb fixing	70 ÷ 110 °C	ON/OFF + service, gold plated	Ø 5 x 90	Cu	1500	Cu + PVC	50
* price and delivery time upon request							