















Filter pressure regulator, Series NL4-FRE

- G 1/2 G 3/4
- filter porosity 5 µm
- with pressure gauge
- suitable for ATEX



Type	1-part, Can be assembled into blocks
Parts	Filter pressure regulator
Mounting orientation	vertical
Certificates	suitable for ATEX
Working pressure min./max.	1,5 ... 16 bar
Ambient temperature min./max.	-10 ... 60 °C
Medium temperature min./max.	-10 ... 60 °C
Medium	Compressed air Neutral gases
Nominal flow Qn	6900 l/min
Regulator type	Diaphragm-type pressure regulator
Regulator function	with relieving air exhaust
Adjustment range min./max.	0,5 ... 10 bar
Pressure supply	single
Filter reservoir volume	50 cm ³
Filter element	exchangeable
Weight	See table below

Technical data

Part No.		Port	filter porosity	Flow Qn	Condensate drain
					Condensate drain
0821300350		G 1/2	5 µm	6900 l/min	semi-automatic, open without pressure
0821300351		G 1/2	5 µm	6900 l/min	semi-automatic, open without pressure
0821300352		G 1/2	5 µm	6900 l/min	semi-automatic, open without pressure
0821300353		G 1/2	5 µm	6900 l/min	fully automatic, open without pressure
0821300354		G 1/2	5 µm	6900 l/min	fully automatic, open without pressure
0821300355		G 1/2	5 µm	6900 l/min	fully automatic, open without pressure
0821300380		G 3/4	5 µm	6900 l/min	semi-automatic, open without pressure
0821300381		G 3/4	5 µm	6900 l/min	semi-automatic, open without pressure
0821300382		G 3/4	5 µm	6900 l/min	semi-automatic, open without pressure
0821300383		G 3/4	5 µm	6900 l/min	fully automatic, open without pressure
0821300384		G 3/4	5 µm	6900 l/min	fully automatic, open without pressure
0821300385		G 3/4	5 µm	6900 l/min	fully automatic, open without pressure

Part No.	Pressure gauge	Reservoir	Protective guard	Weight
0821300350	with pressure gauge	Polycarbonate	-	1,19 kg
0821300351	with pressure gauge	Polycarbonate	Steel	1,28 kg
0821300352	with pressure gauge	Die cast zinc	-	1,41 kg
0821300353	with pressure gauge	Polycarbonate	-	1,26 kg
0821300354	with pressure gauge	Polycarbonate	Steel	1,35 kg

Part No.	Pressure gauge	Reservoir	Protective guard	Weight
0821300355	with pressure gauge	Die cast zinc	-	1,47 kg
0821300380	with pressure gauge	Polycarbonate	-	1,19 kg
0821300381	with pressure gauge	Polycarbonate	Steel	1,28 kg
0821300382	with pressure gauge	Die cast zinc	-	1,41 kg
0821300383	with pressure gauge	Polycarbonate	-	1,26 kg
0821300384	with pressure gauge	Polycarbonate	Steel	1,35 kg
0821300385	with pressure gauge	Die cast zinc	-	1,47 kg

Nominal flow Q_n with secondary pressure $p_2 = 6$ bar at $\Delta p = 1$ bar

Suitable for use in Ex zones 1, 2, 21, 22., Metal protective guard can be retrofitted for all polycarbonate reservoirs, Pressure gauge enclosed separately

Technical information

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

Suitable for use in Ex zones 1, 2, 21, 22.

Note: Polycarbonate reservoirs are susceptible to solvents, supplementary information can be found at "Customer information".

A change in the flow direction (from air supply on the left to air supply on the right) occurs by rotating installation by 180° about the vertical axis. Please see the operating instructions for further details.

Also suitable for separation of fluid oil or water due to the design.

The rear pressure gauge connection on the pressure regulator is closed with a blanking plug, the front connection is open. Depending on the customer application, a second blanking plug may be necessary. Please order separately (see accessories).


Max. achievable compressed air class acc. to ISO 8573-1:2010 6 : 7 : -

Technical information

Material	
Housing	Die cast zinc
Front plate	Acrylonitrile butadiene styrene
Seals	Acrylonitrile butadiene rubber
Threaded bushing	Die cast zinc
Reservoir	Polycarbonate Die cast zinc
Protective guard	Steel
Filter insert	Polyethylene

Dimensions

Dimensions



- A1 = input
- A2 = output
- A6 = output
- A7 = condensate drain
- 1) Semi-automatic condensate drain
- 2) fully automatic condensate drain


Dimensions in mm

A1	A2	A6	A7	B	B1	C	D	E	G	H	I	J	K	L	M	N	N1	O	P	R
G 1/2	G 1/2	G 1/4	G 1/8	69.6	1.8	98.3	146.5	244.8	M50x1,5	54	5.5	69	54.5	46	3	3	5.5	50	20	6.4
G 3/4	G 3/4	G 1/4	G 1/8	69.6	1.8	98.3	146.5	244.8	M50x1,5	54	5.5	69	54.5	46	3	3	5.5	50	20	6.4

S	T	T2	T6	T7	U	V	W	W1
10	13	13	7	8.5	24	18	262.8	67
10	13	13	7	8.5	24	18	262.8	67

Diagrams


Pressure characteristics curve



p1 = working pressure
 p2 = secondary pressure

q = flow rate

Flow rate characteristic



p_1 = Working pressure
 p_2 = Secondary pressure
 q_n = Nominal flow

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



[Emerson.com](https://www.emerson.com)



[Facebook.com/EmersonAutomationSolutions](https://www.facebook.com/EmersonAutomationSolutions)



[LinkedIn.com/company/Emerson-Automation-Solutions](https://www.linkedin.com/company/Emerson-Automation-Solutions)



[Twitter.com/EMR_Automation](https://twitter.com/EMR_Automation)

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™