

TG200 Control thermostat, pin adjustment

DESCRIPTION

Compensated versions available on request

Contact Rating 16(4)A 250Vca, with gold plated contacts 100mV 0,3A.

Gas filled sensing element versions available on request (TG200-Z).

Gold-plated contact versions available on request.

DATASHEET

ADJUSTMENT RANGE/ CALIBRATION (°C)	CONTACTS		BULB		CAPILLARY		CODE
	SPST	SPDT	dimensions (mm)	material	length (mm)	material	
-35 + 35		•	Ø 6,5 x 83	Cu	1500	Cu + PVC	711-F1338-00A
0 + 40		•	Ø 6,5 x 100				711-S1338-00A
0 + 90		•	Ø 6,5 x 73				711-11338-00A*
0 + 120		•					711-71338-00A
0 + 210		•	Ø 5 x 80				Cu
0 + 300		•	Ø 3 x 190	Stainless steel	Stainless steel	711-H1337-00A	
Kit - thermostat completed with frame, knob, screws, knob blocking spring - single packed							
0 + 90		•	Ø 6,5 x 73	Cu	1500	Cu + PVC	711-11338-04A*
0 + 120		•					711-71338-03A
Special versions for HOT WATER CLEANERS - with M14x1 connector							
OFF/90		•	Ø 6 x 75	Cu	1500	Cu + PVC	711-X1338-02A
OFF/120		•					711-71338-02A
OFF/150		•					711-X1338-01A
Special version for FRYER MACHINES - with G 1/4 connector							
0/210	gold plated		Ø 5 x 100	Stainless steel	1000	Stainless steel	713-G1227-01A
Special version 62 + 82 - with G 1/4 connector							
62 + 82		•	Ø 6 x 80	Cu	1000	Cu + PVC	711-X7328-03A

* ISPEL approved

